

Floor Restorative Cleaning Process



You'll Need:

1. A machine scrubber (low speed swing machine or autoscrubber) with an appropriate brush.*
2. A mop bucket with a quality mop & side wringer.
3. EnviroX LVT Renew™
4. EnviroX LVT Renew™ Dispenser
5. 1 Gallon Pump-Up Sprayer
6. Medium duty deck brush

* Refer to the flooring manufacturer's recommendations to determine type of brush needed for flooring type.

1. Pre Spray

Use Pump-Up Sprayer to spray LVT Renew™ **Heavy Duty Red® dilution** on floor in an area large enough to work before it dries. **Let dilution dwell on floor for 5 - 10 minutes.**



2. Machine Scrub

Refer to the flooring manufacturer's recommendations to determine type of brush needed for flooring type and attach the brush to the machine. Machine scrub the area treated with LVT Renew™ **Heavy Duty Red® dilution** in the direction of the grain. When done scrubbing, turn on the vacuum to allow squeegee to remove slurry.

In heavily soiled high traffic areas this process may need to be repeated until all visible soil is removed from the floor.



3. Deck Brush

Use a medium deck brush to scrub hard to reach areas and base boards. Make sure to repeat step one and pre-spray desired area.



4. Pick Up & Rinse

Pick up the soiled product solution and rinse the area using either a mop & bucket or an autoscrubber filled with clean water.



Pure Crafted®

ENVIROX®
A Healthier Way to Clean®

Detailed Restorative Process

Please follow steps in order:

1. Before starting, please post appropriate floor warning signs and close off areas per SOP's.
2. Fill the Pump-Up Sprayer with the **Heavy Duty Red® dilution** of EnvirOx LVT Renew™. Do this by pressing and holding the **Heavy Duty Red®** button on the EnvirOx LVT Renew™ Dispenser.
3. Fill the autoscrubber with clear cold water.
4. Install a light bristle brush to autoscrubber.
Follow flooring manufacturer's recommendations to determine type of brush needed for flooring type.
5. With Pump Up Sprayer, spray LVT Renew™ **Red® dilution** on the floor in an area large enough to work before it dries.
6. Let the LVT Renew™ **Red® dilution** dwell on the floor for 5 - 10 minutes.
7. Run the autoscrubber over the area treated with EnvirOx LVT Renew™ **Red® dilution** in the direction of the grain.
8. The brush works with the LVT Renew™ to loosen the soiled residue from the floor while the water rinse & squeegee removes the soil load from the floor.
9. In heavily soiled high traffic areas this process may need to be repeated until all visible soil is removed from the floor.
10. Use the deck brush to reach hard to reach areas and base boards – spray LVT Renew™ **Red® dilution** on floor, let dwell 5 -10 minutes and scrub with deck brush.
11. If using a swing machine, pick up excess solution and soiled water with a mop and bucket system. Rinse the area with clear water using the mopping system.

Additional Information:

- Initial restorative process for heavily soiled floors will take longer than subsequent uses and require several overlapping passes of the scrubber.
- Future restorations will be easier and less frequently needed if EnvirOx LVT Renew™ **Green® dilution** and a mopping system is used daily.
- Use deck brush and solution to scrub hard to reach areas.
- Please consult flooring manufacturers manual for detailed maintenance requirements.



Questions?

Call 1-800-281-9604 or visit enviroxclean.com



ACW-119-2